



1. PLASTIC FIBER CORB (PMMA):OD=0.98mm
2. CLAD (FLUORD POL YMER) :OD=1.0mm
3. PRIMARY JACKET PE,OD=2.2 mm (BLACK)
4. OUTER JACKET PVC, BLACK IN COLOR, OD=4.0 mm

Chart A

NOTES:

1. Marking: Bewired Toslink Plastic Fiber 4.0mm PVC Black
 2. CABLE: 4.0mm PLASTIC OPTICAL FIBER CABLE
 3. CONNECTORS: TOSLINK TO TOSLINK
 4. PACKING: 1PC PER PE BAG+ 1PC TAG
 5. PERFORMANCE:
 - $L \leq 2M$: ATTENUATION SHOULD BE 2.0dB OR LESS
 - $L > 2M$: ADD 0.2dB/M
- (TEST BY 650±30nm LED LIGHT SOURCE / POWER METER)

1	4.0mm PLASTIC OPTICAL FIBER CABLE	L	M
NO	DESCRIPTION	Q'TY	UNIT

REV.	TOLENRANCE	DESCRIPTION	DATE
	INCHES		
	M/M		
.X	.015		
.XX	.010		
.XXX	.005		
	.05		
DRAWN BY		P/N :	
CHECK BY		SCALE NONE	
APPD BY		UNIT MM	
DATE 2012.07.06		DRAWING NO.: B11-CC001403	
		REV. AO 1/1	



TITLE: VALUE Toslink Cable M-M, 10.0M