

PRODUCT DATASHEET

SPYLUX White

SPYLUX | Little helpers



PRODUCT BENEFITS

- Can be removed from the holder for use as a portable light

PRODUCT FEATURES

- Battery operated dustproof and splashproof luminaire
- Rotating head for versatile use
- Integrated motion sensor



TECHNICAL DATA


Electrical data

Nominal wattage	0.3 W
Nominal voltage	4.5 V

Photometrical data

Color temperature	3000 K
Luminous flux	17 lm
Light color (designation)	Warm white
Color rendering index Ra	>85

Dimensions & weight



Diameter	68.0 mm
Product weight	116.00 g

Colors & materials

Body material	Polycarbonate (PC)
Product color	White

Temperatures & operating conditions

Ambient temperature range	0...+25 °C
----------------------------------	------------

Capabilities

Type of installation	Surface-mounted
Adjustable	Yes
Dimmable	No
Type of sensor	Passive infrared (PIR)

Certificates & standards

Protection class	III
-------------------------	-----

Type of protection	IP43
Standards	CE

COUNTRY SPECIFIC INFORMATION

Product code	METEL code	SEG-No.	STK number	UK Org
4008321935021	OSRSPYLUXWT	-	8771181	-

EQUIPMENT / ACCESSORIES

- Can be mounted with screws, adhesive strip or magnet

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321935021	SPYLUX White	Blister 1	180 mm x 85 mm x 140 mm	2.14 dm ³	154.00 g
4008321935038	SPYLUX White	Shipping carton box 6	258 mm x 194 mm x 218 mm	10.91 dm ³	1133.00 g
4008321935045	SPYLUX White	Shipping carton box 36	477 mm x 314 mm x 253 mm	37.89 dm ³	4568.25 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.