

# PRODUCT DATASHEET

## TubeKIT Value 8.9 W/830 600 mm

SubstiTUBE KIT | Linear luminaires



### AREAS OF APPLICATION

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Shelves, furniture integration or under cabinet mounting
- Direct or indirect lighting (e.g. cove lighting)
- Kitchens, workspaces

### PRODUCT BENEFITS

- Easy to use and multifunctional LED batten luminaire
- All required accessories included (screws, dowels, brackets, hook)
- Ready for connection due to integrated on/off switch and cable with EU-plug
- Bright, robust and durable
- Energy savings of up to 65 % comp. to luminaires using T8 fluorescent lamps on CCG
- Homogeneous light output

### PRODUCT FEATURES

- Durable and energy-saving LED luminaire
- Mercury-free and RoHS compliant
- Clip-In technology for stationary use and hook for mobile use
- Lifetime: up to 30,000 h
- Not dimmable
- Polycarbonate housing



- Uniform illumination
- Available with luminous flux up to 750 lm, 1,700 lm, 2,000 lm (model dependent)
- Color temperatures: 3,000 K, 4,000 K
- Color rendering index  $R_a \geq 80$

## TECHNICAL DATA

### Electrical data

|                 |             |
|-----------------|-------------|
| Nominal wattage | 8.9 W       |
| Nominal voltage | 220...240 V |
| Mains frequency | 50/60 Hz    |

### Photometrical data

|                           |            |
|---------------------------|------------|
| Color temperature         | 3000 K     |
| Luminous flux             | 720 lm     |
| Light color (designation) | Warm white |
| Color rendering index Ra  | >80        |

### Dimensions & weight

|                |          |
|----------------|----------|
| Length         | 600.0 mm |
| Width          | 35.0 mm  |
| Diameter       | 30.0 mm  |
| Height         | 36.5 mm  |
| Product weight | 183.00 g |

### Colors & materials

|               |                    |
|---------------|--------------------|
| Body material | Polycarbonate (PC) |
| Product color | White              |

### Temperatures & operating conditions

|                           |              |
|---------------------------|--------------|
| Ambient temperature range | -20...+45 °C |
|---------------------------|--------------|

### Lifespan

|          |         |
|----------|---------|
| Lifespan | 30000 h |
|----------|---------|

### Additional product data

|                |                                  |
|----------------|----------------------------------|
| Product remark | In development, data preliminary |
|----------------|----------------------------------|

### Capabilities

|                    |                      |
|--------------------|----------------------|
| Dimmable           | No                   |
| Type of connection | Cable with Euro plug |
| Holder designation | G5                   |

## Certificates &amp; standards

|                    |      |
|--------------------|------|
| Protection class   | II   |
| Type of protection | IP20 |
| Standards          | CE   |

## EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

## LOGISTICAL DATA

| Product code  | Product description            | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume                | Gross weight |
|---------------|--------------------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4052899948068 | TubeKIT Value 8.9 W/830 600 mm | Shipping carton box<br>8     | 886 mm x 191 mm x<br>95 mm           | 16.08 dm <sup>3</sup> | 2776.00 g    |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.