

# **PRODUCT DATASHEET**TubeKIT Value 19 W/830 1200 mm

# **SubstiTUBE KIT | Linear luminaires**



## **AREAS OF APPLICATION**

- Indoor applications
- Corridors, entrance areas, stairwells, living rooms, basements
- Shelves, furniture integration or under cabinet mounting
- Direct or indirect lighting (e.g. cove lighting)
- Kitchens, workspaces

## **PRODUCT BENEFITS**

- Easy to use and multifunctional LED batten luminaire
- All required accessories included (screws, dowels, brackets, hook)
- Ready for connection due to integrated on/off switch and cable with EU-plug
- Bright, robust and durable
- Energy savings of up to 65 % comp. to luminaires using T8 fluorescent lamps on CCG
- Homogeneous light output

## **PRODUCT FEATURES**

- Durable and energy-saving LED luminaire
- Mercury-free and RoHS compliant
- Clip-In technology for stationary use and hook for mobile use
- Lifetime: up to 30,000 h
- Not dimmable
- Polycarbonate housing



- Uniform illumination
- Available with luminous flux up to 750 lm, 1,700 lm, 2,000 lm (model dependent)
- Color temperatures: 3,000 K, 4,000 K
- Color rendering index  $R_a$ :  $\geq 80$

# **TECHNICAL DATA**

#### Electrical data

Nominal wattage	19 W	
Nominal voltage	220240 V	
Mains frequency	50/60 Hz	

#### Photometrical data

Color temperature	3000 K	
Luminous flux	1530 lm	
Light color (designation)	Warm white	
Color rendering index Ra	>80	

# Dimensions & weight

Length	1200 mm
Width	35.0 mm
Diameter	30.0 mm
Height	36.5 mm
Product weight	253.00 g

# Colors & materials

Body material	Polycarbonate (PC)	
Product color	White	

# Temperatures & operating conditions

Ambient temperature range	-20+45 °C
---------------------------	-----------

# Lifespan

Lifespan	30000 h
----------	---------

# Additional product data

Product remark	In development, data preliminary

# Capabilities

Dimmable	No	
Type of connection	Cable with Euro plug	
Holder designation	G5	

#### Certificates & standards

Protection class	II
Type of protection	IP20
Standards	CE

## **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included

#### **LOGISTICAL DATA**

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899948082	TubeKIT Value 19 W/830 1200 mm	Shipping carton box 8	1486 mm x 191 mm x 95 mm	26.96 dm³	3990.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.