

PRODUCT DATASHEET SST Duo Click Dim CLAS B 40 5.5 W/827 E14

LED DUO CLICK DIM CLASSIC B | LED lamps with two-step dimming



AREAS OF APPLICATION

- Wherever dimming was originally not planned
- Residential interiors
- Hospitality
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Easy dimming with double click of wall switch
- Easy and cost-effective operation, no dimmer required
- Low energy consumption
- Easy relamping thanks to compact design
- Instant 100 % light, no warm-up time
- Makes rooms multi-purpose with adjustable light atmosphere

PRODUCT FEATURES

- Provides modes for 100 % and 30 % light output
- Controllable via standard wall switch
- Good quality of light; color rendering index R_a : ≥ 80
- Mercury-free lamps



TECHNICAL DATA


Electrical data

Rated wattage	5.50 W
Nominal wattage	5.50 W
Nominal voltage	220240 V
Operating frequency	5060 Hz

Photometrical data

Rated color temperature	2700 K
Color rendering index Ra	≥80
Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Warm White
Nominal luminous flux	470 lm

Dimensions & weight



Overall length	103.0 mm
----------------	----------

Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h
Number of switching cycles	100000

Additional product data

Base (standard designation)	E14
Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

Capabilities

Dimmable	No

Country specific categorizations

ILCOS	DRBB/F-5,5/827-220-240-E14-36	
Order reference	LEDSCLB402XD5,5	

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075814912	SST Duo Click Dim CLAS B 40 5.5 W/827 E14	Shipping carton box 6	262 mm x 153 mm x 136 mm	5.45 dm ³	518.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.