

PRODUCT DATASHEET

ST8S-UN 19 W/3000 1500 mm

SubstiTUBE Star UN | LED tubes for electronic and electromagnetic control gears



AREAS OF APPLICATION

- General illumination within ambient temperatures from -20...+45 °C
- Corridors, stairways, parking garages
- Cooling and storage rooms
- Warehouses

PRODUCT BENEFITS

- Also suitable for operation at low temperatures
- Easy installation
- No bending thanks to glass technology

PRODUCT FEATURES

- Mercury-free and RoHS compliant
- Type of protection: IP20
- Lifetime: up to 30,000 h
- Compatible with conventional and many common electronic control gears (see also compatibility list) and line voltage



TECHNICAL DATA

Electrical data

Nominal wattage	19.00 W
Rated wattage	19.00 W
Nominal voltage	220...240 V
Operating frequency	50...60 Hz
Nominal current	0.09 A
Type of current	AC
Power factor λ	> 0.90

Photometrical data

Light color (designation)	Warm White
Rated color temperature	3000 K
Nominal luminous flux	1800 lm
Rated luminous flux	1800 lm
Color rendering index Ra	≥ 80
Lumen main.fact.at end of nom.life time	0.70
Color temperature	3000 K
Luminous flux	1800 lm
Color rendering index Ra	≥ 80
Standard deviation of color matching	≤ 6 sdcn

Light technical data

Starting time	< 0.5 s
Warm-up time (60 %)	< 0.50 s
Rated beam angle (half peak value)	160.00 °

Dimensions & weight



Length with base excl. base pins/connection	1498.00 mm
---	------------

Tube diameter	26.7 mm
Base diameter	28.0 mm
Product weight	260.00 g
Overall length	1513 mm

Temperatures & operating conditions

Ambient temperature range	-20...+45 °C
Maximum temperature at tc test point	52 °C

Lifespan

Lifespan	30000 h
Nominal lamp life time	30000 h
Rated lamp life time	30000 h
Number of switching cycles	100000

Additional product data

Base (standard designation)	G13
Mercury-free	Yes

Capabilities

Dimmable	No
-----------------	----

Certificates & standards

Type of protection	IP20
Standards	CE
Energy efficiency class	A+
Energy efficiency class	A+
Energy consumption	19 kWh/1000h

Country-specific categorizations

Order reference	ST8S-1.5M 19W/8
------------------------	-----------------

Logistical data

Temperature range at storage	-20...80 °C
-------------------------------------	-------------

SAFETY ADVICE

Operation in outdoor applications in suitable damp-proof luminaires possible according to data sheet and installation instruction.

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075137349	ST8S-UN 19 W/3000 1500 mm	Shipping carton box 8	1660 mm x 182 mm x 125 mm	37.77 dm ³	4772.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For current information see

▶ www.ledvance.com/substitute

LEGAL ADVICE

When used to replace a T8 fluorescent lamp the total energy efficiency and light distribution depends on the design of the lighting system.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.