

	Model	Reolink Go
Hardware Features	Image Sensor	Starlight CMOS Image Sensor
	Display Resolution	1920 x 1080 (2.0Megapixel)
	Lens	f=2.9mm Fixed, F=1.83, With IRCUT
	Angle of View	Horizontal: 130°, Vertical: 70°
	PIR Detecting Distance	Low: 2-4 Meters, Mid: 4-6 Meters, High: 6-10 Meters
	PIR Detecting Angle	Horizontal: 120°
	Minimum Illumination	0 Lux (With IR Illuminator)
	IR Distance	Up to 10 Meters (33Feet)
	Dimensions	Φ75 x 113mm
	Weight(battery included)	380g
	Interface	
		Built-in Micro SIM Card Slot
		Built-in Microphone and Speaker
		Micro USB Battery Charge Interface
		Reset Button
Software Features	Protocols & Standards	SSL, TCP/IP, UDP, SMTP, DHCP, DNS, P2P,HTTP,PPP,MMS
	Image Compression	H.264
	Maximal Frame Rate	15fps
	Code Rate	64Kbps ~ 1576Kbps
	Audio	Two-way Audio
	Maximal User Access	2 Users
	Browser Supported	Not Available
	OS Supported	Smartphone: iOS, Android
	Standby Awaken	PIR Alarm, Remote Access, Reset Button
Record Mode	PIR Alarm Record	
3G/4G	Frequency Bands	B2/B4/B5(A)B1/B5(AUV)B1/B5/B8(E)@WCDMA, B2/B4/B12(A) B1/B3/B5/B7/B28(AUV) B1/B3/B5/B7/B8/B20(E)@LTE
	Transmission Data	HSPA R6: Max 14.4Mbps (DL)/Max 5.76Mbps (UL), LTE CAT1: Max 10Mbps (DL)/Max 5Mbps (UL)
Battery	Type Specification	18650 lithium battery/3.6V, 7800mAH, Supports Solar Power
	Battery Level Indication	Yes
	Ordinary Life	1-3 Months
	Endurance Ability	Upto 3 Months in Standby Mode, or 600 Minutes of Live View or PIR Moiton Detected Recording
Other Parameters	Temperature	Operating Temperature : -10℃~+55℃
	Humidity	Operating Humidity: 20% ~ 85%
	Waterproof Level	Weatherproof