



IB836BA-HT/EHT



IB836BA-HF3/EHF3

Bullet Network Camera



2MP · WDR Pro · SNV · 30M IR · Smart IR · IP66 · IK10 ·
Extreme Weather · Video Rotation · Defog

VIVOTEK's IB836BA-H is a series of outdoor-ready Full HD bullet network cameras offering superb video quality with up to 30 fps at 1920x1080. Featuring VIVOTEK's WDR Pro and SNV technology, the series is capable of capturing high quality and high visibility video whether in high contrast or low light environments.

The IB836BA-H series provides flexible options for both fixed focus for simple operation, and remote focus with built-in stepping motors and P-iris to provide precise adjustments remotely. In order to adapt to constantly changing outdoor lighting conditions, the IB836BA-H series features a removable IR-cut filter as well as IR illuminators effective up to 30M for superior image quality around the clock. As a professional day/night camera, the IB836BA-H series also adopts a Smart IR technology which prevents overexposure and provides noise reduction to adjust the IR lighting intensity instantaneously based on the changes of light in the ambient environment.

For protection against harsh outdoor environments, the IB836BA-H series is encased in a weather-proof IP66-rated housing, making it impervious to rain and dust. The robustness of the IB836BA-H series is further strengthened by the adoption of rugged IK10 design housing.

Additionally, a wide operating temperature range further enhances the IB836BA-H's performance and reliability in extremely cold or hot temperatures, even when using PoE. When choosing VIVOTEK IB836BA-H series, users have four options: the IB836BA-HT, IB836BA-EHT, IB836BA-HF3, and IB836BA-EHF3. Different options can be chosen based on the requirements of your application, such as focusing method or operating environment temperature.


Key Features

- 2-Megapixel CMOS Sensor
- 30 fps @ 1920x1080
- 2.8 ~ 12 mm, Vari-focal, Remote Focus, P-iris Lens (IB836BA-HT/EHT)
- Removable IR-cut Filter for Day & Night Function
- Built-in IR Illuminators, Effective up to 30 Meters
- Smart IR Technology to Avoid Overexposure
- WDR Pro for Unparalleled Visibility in Extremely Bright and Dark Environments
- SNV (Supreme Night Visibility) for Low Light Conditions
- 3D Noise Reduction
- Video Rotation for Corridor View
- Weather-proof IP66 and Vandal-proof IK10-rated Housing
- Extreme Weather Support with PoE (IB836BA-EHT/EHF3)





Technical Specifications

Model	IB836BA-HT: Vari-focal, P-iris, Remote Focus IB836BA-EHT: Vari-focal, P-iris, Remote Focus, Extreme Weather IB836BA-HF3: Fixed-focal IB836BA-EHF3: Fixed-focal, Extreme Weather
System Information	
CPU	Multimedia SoC (System-on-Chip)
Flash	1Gb
RAM	2Gb
Camera Features	
Image Sensor	1/2.7" Progressive CMOS
Maximum Resolution	1920x1080 (2MP)
Lens Type	IB836BA-HT/EHT: Vari-focal, Remote Focus IB836BA-HF3/EHF3: Fixed-focal
Focal Length	IB836BA-HT/EHT: f = 2.8 ~ 12 mm IB836BA-HF3/EHF3: f = 3.6 mm
Aperture	IB836BA-HT/EHT: F1.8 ~ F2.85 IB836BA-HF3/EHF3: F2.1
Auto-iris	P-iris (IB836BA-HT/EHT)
Field of View	IB836BA-HT/EHT: 34° ~ 112° (Horizontal) 19° ~ 59° (Vertical) 39° ~ 133° (Diagonal) IB836BA-HF3/EHF3: 90° (Horizontal) 46° (Vertical) 108° (Diagonal)
Shutter Time	1/5 sec. to 1/32,000 sec.
WDR Technology	WDR Pro
Day/Night	Removable IR-cut filter for day & night function IB836BA-HT/EHT:
Minimum Illumination	0.1 Lux @ F1.8 (Color) 0.01 Lux @ F1.8 (B/W) IB836BA-HF3/EHF3: 0.16 Lux @ F2.1 (Color) 0.01 Lux @ F2.1 (B/W)
Pan/Tilt/Zoom Functionalities	ePTZ: 48x digital zoom (4x on IE plug-in, 12x built in)
IR Illuminators	Built-in IR illuminators, effective up to 30 meters with Smart IR IR LED*8
On-board Storage	Slot type: SD/SDHC/SDXC card slot Seamless Recording
Video	
Compression	H.264 & MJPEG
Maximum Frame Rate	30 fps @ 1920x1080 In both compression modes
Maximum Streams	4 simultaneous streams
S/N Ratio	66dB
Dynamic Range	100dB
Video Streaming	Adjustable resolution, quality and bitrate Smart Stream
Image Settings	Adjustable image size, quality and bit rate; Time stamp, text overlay, flip & mirror; Configurable brightness, contrast, saturation, sharpness, white balance, exposure control, gain, backlight compensation, privacy masks; Scheduled profile settings, 3D noise reduction, video rotation, defog
Audio	
Audio Capability	Two-way Audio (full duplex)
Compression	G.711, G.726
Interface	External microphone input Audio output
Network	
Users	Live viewing for up to 10 clients
Protocols	IPv4, IPv6, TCP/IP, HTTP, HTTPS, UPnP, RTSP/RTP/RTCP, IGMP, SMTP, FTP, DHCP, NTP, DNS, DDNS, PPPoE, CoS, QoS, SNMP, 802.1X, UDP, ICMP, ARP, SSL, TLS, CIFS/SMB
Interface	10Base-T/100 BaseTX Ethernet (RJ-45) *It is highly recommended to use standard Cat. 5e & Cat. 6 cables which are compliant with the 3P/ETL standard.
ONVIF	Supported, specification available at www.onvif.org

Intelligent Video	
Video Motion Detection	Five-window video motion detection
Alarm and Event	
Alarm Triggers	Motion detection, manual trigger, digital input, periodical trigger, system boot, recording notification, camera tampering detection, audio detection
Alarm Events	Event notification using digital output, HTTP, SMTP, FTP, NAS server and SD Card File upload via HTTP, SMTP, FTP, NAS server and SD card
General	
Smart Focus System	Remote Focus (IB836BA-HT/EHT) RJ-45 cable connector for Network/PoE connection Audio input Audio output DC 12V power input Digital input*1 Digital output*1
Connectors	
LED Indicator	System power and status indicator DC 12V
Power Input	IB836BA-HT/HF3: IEEE 802.3af/at PoE Class 0 IB836BA-EHT/EHF3: IEEE 802.3at PoE Class 4
Power Consumption	IB836BA-HT: Max. 13 W IB836BA-EHT/EHF3: Max. 25 W (Heater on) IB836BA-HF3: Max. 9 W
Dimensions	Ø 88 x 293 mm
Weight	Net: 1264 g
Casing	Weather-proof IP66-rated housing (Camera body) Vandal-proof IK10-rated metal housing (Camera body)
Safety Certifications	IB836BA-HT/EHT: CE, LVD, FCC Class A, VCCI, C-Tick, UL IB836BA-HF3/EHF3: CE, LVD, FCC Class A, VCCI, C-Tick
Operating Temperature	IB836BA-HT/HF3: Starting Temperature: -10°C ~ 50°C (14°F ~ 122°F) Working Temperature: -20°C ~ 50°C (-4°F ~ 122°F) IB836BA-EHT/EHF3: Starting Temperature: -40°C ~ 50°C (-40°F ~ 122°F) Working Temperature: -50°C ~ 50°C (-58°F ~ 122°F)
Warranty	IB836BA-HT/EHT: 36 months IB836BA-HF3/EHF3: 24 months
System Requirements	
Operating System	Microsoft Windows 7/8
Web Browser	Internet Explorer 10/11 Chrome version 58.0.3029 or above
Other Players	VLC: 1.1.11 or above Quicktime: 7 or above
Included Accessories	
CD	User's manual, quick installation guide, Shepherd, VAST 32-channel recording software
Others	Quick installation guide, warranty card, sun shield, wall mount bracket, alignment sticker/ desiccant bag, waterproof connector, screw pack
Dimensions	



Compatible Accessories

Mounting Kits			PoE Kits
			
AM-312 Pole Mount Adapter	AM-412 Corner Mount Adapter	AM-714 Junction Box	AP-FXC-0250 Outdoor 2-Port FE PoE Extender