



Datenblatt - Fiche technique - Data sheet

26.99.0170



VALUE 19"-KVM-Switch, 8-Port, 43 cm (17") TFT (4:3), VGA, USB+PS/2,
Tastaturlayout UK

VALUE Switch KVM 19", 8 ports, TFT de 43 cm (17"), VGA, USB et PS/2, UK

VALUE 19" LCD KVM Switch 1 User - 8PCs, 43 cm (17") TFT (4:3), VGA, USB +
PS/2, UK

Item no.: 26.99.0170

VALUE 19" KVM Switch, 43cm, VGA, USB+PS/2, UK Keyboard, 8-port, black color



Features:

- Control platform with LCD, mouse, keyboard and 8 ports KVM switch
- Comptible with PS/2, USB standard interface
- Support VGA, SVGA XGA video input
- Accord with DDC, DDC2, DDC2B standard and VESA standard
- Support resolution 1920 * 1080 (max.)
- 1U height, suitable for 19" standard cabinet installation and metal structure
- 43cm LCD screen with high brightness, high clear and high resolution
- Control platform can be totally pulled out from the cabinet and the LCD screen can be turned on to 120 degrees
- Ultra thin keyboard with keypad, UK layout
- Mouse touch board with two function button
- Front panel with lock to prevent damage by accident
- Built-in power
- Automatic power on/off. When pulling control platform out from cabinet, the power turns off automatically. When pushing it into the cabinet, the power turns on automatically
- Easy to use OSD menu

Specification:

| | | |
|---------------------|----------|---|
| Computer Connection | | 8 |
| CPU Port Selection | | Front panel buttons/OSD menu |
| Console | Keyboard | Disassembled standard 99-key keyboard |
| Connector | Mouse | Standard PS/2 touch pad; rear side with USB connector |

| | | | |
|-------------------------------|----------------------------|---|--|
| | Video | 43cm SXGA color TFT-LCD | |
| Cable Connector | Keyboard | 1 x PS/2 female (purple) , 1 x USB female | |
| | Mouse | 1 x PS/2 female (green) , 1 x USB female | |
| | Video | 1 x HDB-15 male (blue) | |
| LED's | Online | 1 red LED | |
| | Selected | 1 green LED | |
| LCD monitor | monitor | 43cm SXGA Color TFT-LCD | |
| | visible square | 337.92(H)*270.336(V)mm | |
| | Resolution(max) | 1920*1080 60Hz | |
| | Support Color | 16.7M colors (RGB 6-bit +Hi-FRC) | |
| | White Luminance | 250 (center, Typ)@ 60 mA | |
| | contrast | 1000:1 (Typ) | |
| | backlight | LED | |
| | Pixel Pitch | 0.264(per one triad)x0.264 | |
| | LCD MTBF | 50,000hours | |
| | Input power | DC 12V | |
| Mouse | X/Y resolution | 1000dots/inch 40x40/mm) | |
| | hardware connector | Standard PS/2 & USB | |
| | Os support | WIN95/98/98SE/ME/200/XP/VISTA/7/8/NT, UNIX, LINUX | |
| | Using life | >1,000,000 times | |
| Power | Power (AC) | ~100V-240V | |
| | Using life | MTBF>60,000hours 25 °C | |
| Housing color | black | | |
| Housing material | Metal | | |
| Gross weight | 22.74 KGS | | |
| Dimensions | 640*443*42mm | | |
| Rack installation depth | 600mm ~ 1200mm(adjustable) | | |
| Operating/storage Temperature | 0 ~ 50 /-20 ~ 60°C | | |
| PC ports | 8 | | |