



Datenblatt - Fiche technique - Data sheet

26.99.0171



VALUE 19"-KVM-Switch, 8-Port, 43 cm (17") TFT (4:3), VGA, USB+PS/2,
Tastaturlayout D

VALUE Switch KVM 19", 8 ports, TFT de 43 cm (17"), VGA, USB et PS/2, D

VALUE 19" LCD KVM Switch 1 User - 8PCs, 43 cm (17") TFT (4:3), VGA, USB +
PS/2, D

Item no.: 26.99.0171

VALUE 19" KVM Switch, 43cm, VGA, USB+PS/2, German Keyboard, 8-port, black color



Features:

- Control platform with LCD, mouse, keyboard and 8 ports KVM switch
- Comptible with PS/2, USB standard interface
- Support VGA, SVGA XGA video input
- Accord with DDC, DDC2, DDC2B standard and VESA standard
- Support resolution 1920 * 1080 (max.)
- 1U height, suitable for 19" standard cabinet installation and metal structure
- 43cm LCD screen with high brightness, high clear and high resolution
- Control platform can be totally pulled out from the cabinet and the LCD screen can be turned on to 120 degrees
- Ultra thin keyboard with keypad, German layout
- Mouse touch board with two function button
- Front panel with lock to prevent damage by accident
- Built-in power
- Automatic power on/off. When pulling control platform out from cabinet, the power turns off automatically. When pushing it into the cabinet, the power turns on automatically
- Easy to use OSD menu

Specification:

Computer Connection		8
CPU Port Selection		Front panel buttons/OSD menu
Console	Keyboard	Disassembled standard 99-key keyboard
Connector	Mouse	Standard PS/2 touch pad; rear side with USB connector

	Video	43cm SXGA color TFT-LCD	
Cable Connector	Keyboard	1 x PS/2 female (purple) , 1 x USB female	
	Mouse	1 x PS/2 female (green) , 1 x USB female	
	Video	1 x HDB-15 male (blue)	
LED's	Online	1 red LED	
	Selected	1 green LED	
LCD monitor	monitor	43cm SXGA Color TFT-LCD	
	visible square	337.92(H)*270.336(V)mm	
	Resolution(max)	1920*1080 60Hz	
	Support Color	16.7M colors (RGB 6-bit +Hi-FRC)	
	White Luminance	250 (center, Typ)@ 60 mA	
	contrast	1000:1 (Typ)	
	backlight	LED	
	Pixel Pitch	0.264(per one triad)x0.264	
	LCD MTBF	50,000hours	
	Input power	DC 12V	
Mouse	X/Y resolution	1000dots/inch 40x40/mm)	
	hardware connector	Standard PS/2 & USB	
	Os support	WIN95/98/98SE/ME/200/XP/VISTA/7/8/NT, UNIX, LINUX	
	Using life	>1,000,000 times	
Power	Power (AC)	~100V-240V	
	Using life	MTBF>60,000hours 25 °C	
Housing color	black		
Housing material	Metal		
Gross weight	22.74 KGS		
Dimensions	640*443*42mm		
Rack installation depth	600mm ~ 1200mm(adjustable)		
Operating/storage Temperature	0 ~ 50 /-20 ~ 60°C		
PC ports	8		