



PIN OUT			
A1,B1,A12,B12	GND	A1,B1,A12,B12	GND
A4,B4,A9,B9	VBUS	A4,B4,A9,B9	VBUS
A5	CC	A5	CC
B5		B5	B5
A6	Dp1	A6	Dp1
A7	Dn1	A7	Dn1
A2	SSTXp1	B11	SSTXp1
A3	SSTXn1	B10	SSTXn1
B11	SSRXp1	A2	SSRXp1
B10	SSRXn1	A3	SSRXn1
B2	SSTXp2	A11	SSTXp2
B3	SSTXn2	A10	SSTXn2
A11	SSRXp2	B2	SSRXp2
A10	SSRXn2	B3	SSRXn2
A8	SBU1	B8	SBU1
B8	SBU2	A8	SBU2
SHELL		SHELL	

NOTE:

- Electrical test:
 - 100% open short & miss wire test;
 - Insulation resistance:DC 300V 0.1S 10MΩ ;
 - Conductor resistance:3Ω Max;
 - Displayport practical application Test Pass 4k@60HZ
- Feature:

Full-featured USB3.2 Type-C Cable (USB3.2 Gen1x2)
Transmission rate Up to 10Gbps
Resolution 3840*2160@60Hz
Backwards compatible with USB 3.2, 3.0 and 2.0 and Thunderbolt 3
Supports USB power delivery 3.0 60W/3A
Operating Temperature:0℃~45℃
Storage Temperature:-20℃~ 70℃
- RoHS and REACH Compliant

MATERIAL LIST:

④	OVER MOLDING	TPE WHITE	2	
③	SHIELDED	Tinplate	2	
②	USB TYPE C Male	USB 3.2 C/M Solder Type,Black PBT Insulation,The Pin Gold Plating, the shell for Nickel Plating Without E-MARK	2	
①	CABLE	USB3.2 (29AWG BC*2C+AL+HM)*4P+32AWG BC*1P+32AWG BC*4C+24AWG TC*2C+ADB TPE WHITE OD:5.3±0.2mm	L±T	
NO.	PARTS NAME	SPECIFICATION DESCRIPTION	QT'Y	REMARK
		NEW	2024-06-25	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.

11.99.9065	VALUE Cable compatible to USB3.2Gen2, 10Gbit/s, C-C, M/M, 60W, 3m	3000±50mm
11.99.9066	VALUE Cable compatible to USB3.2Gen2, 10Gbit/s, C-C, M/M, 60W, 5m	5000±100mm
ITEM NO.	DESC.	LENGTH

SECOMP