



NOTE:

Standards: RS-232 & CCITT V.24 asynchronous protocol
 Connector: two DB9 on both sides
 Transmission mode: asynchronous full-duplex, full transparent
 Isolated voltage: 2,500Vrms impulse or 500VDC
 Baudrate: 300bps-57,600bps
 Power: from RS-232(TXD, RTS or DTR)
 Operating temperature: -40°C to 85°C
 Relative humidity: 5% to 95%
 ROHS 2.0 and Reach compliant.

MATERIAL LIST:

④	SHELL	ABS Black	1	
③	PCBA	PCB With IC P521+TP7660	1	
②	DB 9 PIN	DB 9 PIN /Male ,Black INSULATION,THE PIN GOLD PLATED ,THE SHELL FOR NICKET PLATED with Nut	1	
①	DB 9 PIN	DB 9 PIN /Female ,Black INSULATION,THE PIN GOLD PLATED ,THE SHELL FOR NICKET PLATED with Screw	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK

SECOMP				
CUSTOMER		ITEM NO.	12.99.1016	
PRODUCT NAME		VALUE Optical Coupler	709016	UNIT MM
DRAWNBY		CHECKBY	APPOBY	DATE
BY	CHK	REVISION RECORD MODIFICATIONS	DATE	REV.
		NEW	2020.09.22	A
Alvan	Alvan		2020.09.22	