


IC485SN

RS-232/RS-485 Interface Converter

 IC485SN is a 2-way converter for converting RS-232 signals to and from RS-422/RS-485 signals in longdistance application up to 1200m (4000 ft.) and needs no external power supply.





Features

- Data transmission controlled by the RTS signal.
- DCE/DTE selectable.
- Point to point, multidrop, and simplex/duplex link selection.
- Four wire full duplex; two wire half duplex.
- Compact size.
- Cable distance of up to 1200m (4000 ft.).
- Non powered operation.
- Supports baud rates up to 115.2kbps.
- OS Support: Windows 2000, Windows XP

Specification

Function		IC485SN
Connectors		1 DB-25 Female (RS-232)
		RS-485 / RS-422 Four Terminal Block
		1x RJ-11 Female
Switches	SW1	DCE, DTE
	SW2	TxON, RxON
		TxRTS, RxON
		TxDTR/RTS, RxDSR/ON
Power Consumption		DC9V, 0.9W (max.)
Signal Range		1200 m [4000'] (max.)
Data Rate		Up to 100 Kbps under 1200 m [4000']
Environment	Operating Temperature	0 – 50°C
	Storage Temperature	-20 – 60°C
	Humidity	0~80% RH, Non-condensing
Physical Properties	Housing	Plastic
	Weight	0.06 kg
	Dimension (L x W x H)	5.40 x 7.45 x 1.85 cm

ATEN International Co., Ltd.

3F., No.125, Sec. 2, Datong Rd., Sijhih District., New Taipei City 221, Taiwan Phone: 886-2-8692-6789 Fax: 886-2-8692-6767 www.aten.com E-mail: marketing@aten.com



Printed 07/2015 V1.0

© Copyright 20154 ATEN® International Co., Ltd. ATEN and the ATEN logo are trademarks of ATEN International Co., Ltd. All rights reserved. All other trademarks are the property of their respective owners