


REV.	
	A/0

Initial

	DRAFTING
	XYH



CHECKED	

Length



CABLE MARKING (NO.930) :


KEMA-KEUR H05VV-F 3x0.75mm² 300/500V ORDINARY DUTY NSW28976 YFC-BonEagle


$$\frac{B}{1.5:1}$$


- Jacket OD: 6.8 ± 0.3 mm

- Insulation OD: 2.4 ± 0.15 mm

- Conductor 0.75mm²x3C


$$\frac{C}{2.5:1}$$

Polarity and Conduction and Puncture Test

Dielectric Voltage Withstand Test : 2000V / 1 Sec

Electrical Performance (20°C)

Item	Parameter
Conductor Resistance	$\leq 26.0\Omega/1000m$
Voltage Rating	AC 300/500V

Customer Item NO.	Cable Color	Molding Color	Length (mm)
19.08.1035	Black	Black	800±15
19.08.1036	Black	Black	1800±30

PINOUT			
SF-04		SF-82K	WIRE
E		E	YE/GN
L		L	BROWN
N		N	BLUE

⑦	Molding	Molding 40P PVC Black	AR
⑥	Spring	0.3×2.5×15mm spring steels	1PC
⑤	Lock	SF-82K Locking part nickel plating	1PC
④	Housing	SF-82K One piece of inner frame C13 Three plug	1SET
③	Terminal	SF-82K IEC C13 Female Three Plug Straight Insert of Common Terminal Brassy Yellow 0.75mm ²	3PCS
②	Terminal	SF-04 One piece of inner frame Nickel plated 0.75 mm ² Black	1PC
①	Cable	H05VV-F 0.75mm ² 3C Black PVC	1PC

Unless specified on the drawing, tolerances are per the follows:

X.	± 0.20	X°	± 3
.X	± 0.10	.X°	± 0.3
.XX	± 0.05		

SECOMP

DRAW. NO	GFAC-S250063	TITLE	H05VV-F 0.75mm² 3C SF-04 TO SF-82K Black CABLE ASSY		
CUSTOMER	矽肯				
CUST'R P/N	--	DRAW	XYH	DATE	2025.03.26
SCALE	1:1	CHECK		DATE	
UNIT	mm	APPROVED		SHEET	1 of 1

GFDY-C200014

Part Number

Note

[illegible]

	D	I
--	---	---

CD	

☐	☐
HF	0.1



UNIT

mm

APPROVED

開發處
2025.03.28

SHEET

1 of 1