



DATE
2025.03.26

REV.	
A/0	

Initial

DRM FING
XYH

CHECKED	



CABLE MARKING (NO.930) :



—Insulation OD: 2.4 ± 0.15 mm

— Conductor 0.75mm²x3C


$$\frac{C}{2.5:1}$$


Item	Parameter
Conductor Resistance	$\leq 26.0\Omega/1000m$
Voltage Rating	AC 300/500V

19.08.1035	Black	Black	800±15
19.08.1036	Black	Black	1800±30

SF-04		SF-82K	WIRE
E		E	YE/GN
L		L	BROWN
N		N	BLUE

④	Housing	SF-82K One piece of inner frame C13 Three plug								1SET
③	Terminal	SF-82K IEC C13 Female Three Plug Straight Insert of Common Terminal Brassy Yellow 0.75mm²								3PCS
②	Terminal	SF-04 One piece of inner frame Nickel plated 0.75 mm² Black								1PC
①	Cable	H05VV-F 0.75mm² 3C Black PVC								1PC
No.	TITLE	DESCRIPTION								Q'TY
Cable Spec NO.		GFDY-C200014	Part Number	—	Note	■ RoHS2.0	■ Reach	□ GP	□ HF	0

X.	± 0.20	X°	± 3
.X	± 0.10	.X°	± 0.3
.XX	± 0.05		

DRAW. NO	GFAC-S250063	TITLE	H05VV-F 0.75mm² 3C SF-04 TO SF-82K Black CABLE ASSY		
CUSTOMER	砂肯				
ST' R P/N	--	DRAW	XYH	DATE	2025.03.26
SCALE	1:1	CHECK		DATE	
UNIT	mm	APPROVED		SHEET	1 of 1