



1	2	3	4	5	6	7	8	9	10	11	12	13	
MOLDING: YU-59									DATE	REV.	REVISION	DRAFTING	CHECKED
									2023.07.13	A/0	NEW	XMM	
									2023.12.22	A/1	Updated The △ Winding Mode	ST	
									2023.12.27	A/2	Updated The △ Cable Marking	ST	



⚠ Marking:roline CAT6A U/UTP PATCH CABLE 34AWGX4P



Note:

1. Channel Test
- 2.100% Test(Open,short,miss wire)
- 3.Contact Resistance:2Ω Max.
- 4.Insulation Resistance:DC/250V,10 MΩ Min. For 0.01s
- 5.Hi-pot Test:AC/250V 5mA Max. For 0.01s
- 6.All Material Meet The RoHS,2.0

PID	Cable Color	Molding Color	Length (mm)
21.15.2190	BK012	BK012	500±20
21.15.2191	BK012	BK012	1000±30
21.15.2192	BK012	BK012	1500±30
21.15.2193	BK012	BK012	2000±30

PINOUT			
P1(T568B)		P2(T568B)	WIRE
1		1	WHITE/ORANGE
2		2	ORANGE
3		3	WHITE/GREEN
6		6	GREEN
4		4	BLUE
5		5	WHITE/BLUE
7		7	WHITE/BROWN
8		8	BROWN

SECOMP

④	Velcro Tape	10mm Wide Black Velcro Tape	1PC
③	Molding	70P PVC	A/R
②	Plug	RJ45 8P8C 50u" Unshielded Hole Diameter OD:0.35mm	2PCS
①	Cable	FLAT CABLE CAT.6A U/UTP 34AWG STR BC PVC	A/R
No.	TITLE	DESCRIPTION	Q'TY
Cable Spec No.	GFWL-C230242	Part Number	--
		Note	
		RoHS 2.0	Reach
		GP	HF
		OT	