



Note:

1. Grade Designation: Each to Reference
2. ROHS 2.0 and REACH Compliant
3. The out jacket is conform to IEC60332-1, EN60754-2, EN 61034-2
4. Min. Bending Radius: Static: 20mm, Dynamic: 40mm

MATERIAL LIST:

|    |  |       |        |
|----|--|-------|--------|
| ⑧  | Fiber Optical Cable Duplex $\phi$ 2.0 OM5 50/125um LSZH Lime Green | L     |        |
| ⑦  | Black Heat shrink tubing   | 2     |        |
| ⑥  | Ring 1, 2  | 4     |        |
| ⑤  | LC 2.0 white Boot  | 4     |        |
| ④  | LC Duplex Clip Lime Green  | 2     |        |
| ③  | LC Duplex Connector Lime Green                                     | 4     |        |
| ②  | LC/UPC MM Ferrule  | 4     |        |
| ①  | LC White Dust cap  | 4     |        |
| NO | SPECIFICATION STANDARD   | QT' Y | REMARK |

|                 |               |
|-----------------|---------------|
| Type            | Multi-Mode    |
| Insertion Loss  | $\leq 0.3$ dB |
| Return Loss     | $\geq 30$ dB  |
| Test Wavelength | 850nm         |

| ITEM NO.   | DESC.   |
|------------|---|
| 21.15.9275 | ROLINE FO Jumper Cable, OM5, OD 2mm, LC/LC, 10m |
| 21.15.9276 | ROLINE FO Jumper Cable, OM5, OD 2mm, LC/LC, 7m  |
| 21.15.9274 | ROLINE FO Jumper Cable, OM5, OD 2mm, LC/LC, 5m  |
| 21.15.9273 | ROLINE FO Jumper Cable, OM5, OD 2mm, LC/LC, 3m  |
| 21.15.9272 | ROLINE FO Jumper Cable, OM5, OD 2mm, LC/LC, 2m  |
| 21.15.9271 | ROLINE FO Jumper Cable, OM5, OD 2mm, LC/LC, 1m  |

|    |     |                               |            |      |
|----|-----|-------------------------------|------------|------|
|    |     | Add Min. Bending Radius       | 2022-1-24  | A1   |
|    |     | NEW                           | 2021-07-09 | A2   |
| BY | CHK | REVISION RECORD MODIFICATIONS | DATE       | REV. |

