

WV-X41701-F1

12.5MP Sensor AI Indoor Fisheye Camera

12.5MP Sensor AI Indoor Fisheye Camera

Coming Soon



- 12.5MP Sensor AI Indoor Fisheye Camera
 - AI Free Text Detection
 - AI Noise Reduction
 - IP44 Certified
 - FIPS 140-3 Level 3, CC EAL6+ (NXP® EdgeLock® SE052F)
 - NDAA Compliant
-

SPECIFICATIONS

Camera	
Image Sensor	Approx. 1/1.6 type CMOS image sensor
Scanning Area	7.04 mm (H) × 7.04 mm (V) {9/32 inches (H) × 9/32 inches (V)}
Minimum Illumination	Color : 0.08 lx (30IRE, F2.0, 1/30 s, AGC: 11)* 0.11 lx (50IRE, F2.0, 1/30 s, AGC: 11) 0.007 lx (50IRE, F2.0, 16/30 s, AGC: 11)* BW : 0.06 lx (50IRE, F2.0, 1/30 s, AGC: 11) 0.004 lx (50IRE, F2.0, 16/30 s, AGC: 11)* * Converted value
Maximum Shutter	[30 fps mode] Max. 1/10000 s to Max. 16/30 s [25 fps mode] Max. 1/10000 s to Max. 16/25 s
AI Auto Exposure	On/Off
AI Noise Reduction	On/Off
Super Dynamic	On/Off (Range : 0 to 31)
Dynamic Range	Max. 120 dB (Super Dynamic: On, Level: 31, 15 fps*) * The frame rate is limited to 15 fps for level 30 or higher.
Image Settings	Gain (AGC), White Balance
Image Compensation	Adaptive black stretch, Back light compensation (BLC), Fog compensation, High light compensation (HLC), Digital noise reduction
Color/BW (ICR)	Off/ On/ Auto1(Normal)/ Auto2(IR Light)/ Auto3(SCC)
IR LED Light	-
White LED Light	-
Video Motion Detection (VMD)	On/ Off (4 areas available)
Scene Change Detection (SCD)	On/ Off (1 area available)
Audio Detection	On/ Off
AI Sound Classification	Selectable from Gunshot, Yell, Vehicle horn, Glass break
Analytics	AI-VMD, AI Scene Change Detection, AI On-site Learning, AI Processing Relay, AI Privacy Guard, AI Free Text Detection, For details : https://i-pro.com/products_and_solutions/en/surveillance/products/analytics-software 3rd party applications are also available. https://i-pro.com/products_and_solutions/en/surveillance/solutions/edge-ai-platform/application-list
Maximum No. of Applications	9 (AI app)
Docker	Yes
Privacy Zone	On/Off (Up to 8 zones available) mosaic
VIQS	On/Off (Up to 8 zones available)
Image Rotation	0° (Off)/ 90°/ 180° (Upside-down)/ 270° *Fisheye mode only 0° (Off)/ 180° (Upside-down) *Except Fisheye mode

Camera Title (OSD)	On/ Off Up to 20 characters (alphanumeric characters, marks)
--------------------	---

Lens	
Optical Zoom	-
Digital (electronic) Zoom	-
Focal Length	1.7 mm {1/15 inches}
Angular Field of View	Horizontal: 181° Vertical: 181°
Adjusting Angle	- 170° to +170 °
Maximum Aperture Ratio	F2.0
Focus Range	0.5 m {19-11/16 inches} - ∞
Aperture Range	F2.0

DORI	
Distance to the object in the center of the image	Detect (25ppm / 8ppf) : 34.0 m {111.5 ft} Observe (62.5ppm / 19ppf) : 13.6 m {44.6 ft} Recognize (125ppm / 38ppf) : 6.8 m {22.3 ft} Identify (250ppm / 76ppf) : 3.4 m {11.2 ft}
Coverage radius when mounted at a height of 3 m (10 ft)	Detect (25ppm / 8ppf) : 64.2 m {210.5 ft} Observe (62.5ppm / 19ppf) : 23.9 m {78.3 ft} Recognize (125ppm / 38ppf) : 10.1 m {33.2 ft} Identify (250ppm / 76ppf) : 2.3 m {7.5 ft}

System on Chip	
System on Chip (SoC)	Ambarella CV72

Browser GUI	
GUI / Setup Menu Language	English, Italian, French, German, Spanish, Portuguese, Russian, Chinese, Japanese
Browser *1	Microsoft Edge, Firefox, Google Chrome

Network	
Network IF	10Base-T / 100Base-TX, RJ45 connector
Resolution <Ceiling> <Wall>	•Fisheye mode (max. 30 fps/25 fps) 3520×3520 / 2992×2992 / 2192×2192 / 1280×1280 / 640×640 / 320×320 •Quad PTZ mode (max. 30 fps/25 fps), 3584x2688 / 2560×1920 / 2048×1536 / 1600×1200 / 1280×960 / 800×600 / VGA / QVGA •Fisheye + Single PTZ mode (max. 30 fps/25 fps) (Fisheye) 2992×2992 / 2192×2192 / 1280×1280 / 640×640 / 320×320 (Single PTZ) 1600x1200 / 1280×960 / 800×600 / VGA / QVGA
Resolution <Ceiling>	•Double Panorama mode (max. 30 fps/25 fps) 3840x2160 / 2560×1440 / 1920×1080 / 1280×720 / 640×360 / 320×180 •Corridor mode (max. 30 fps/25 fps) 3840x2160 / 2560×1440 / 1920×1080 / 1280×720 / 640×360 / 320×180 •Fisheye + Double Panorama mode (max. 30 fps/25 fps) (Fisheye) 2992×2992 / 2192×2192 / 1280×1280 / 640×640 / 320×320 (Double Panorama) 1920x1080 / 1280×720 / 640×360 / 320×180 •Fisheye + Corridor (max. 30 fps/25 fps) (Fisheye) 2992×2992 / 2192×2192 / 1280×1280 / 640×640 / 320×320 (Corridor) 1920x1080 / 1280×720 / 640×360 / 320×180 •Fisheye + Quad PTZ mode (max. 30 fps/25 fps) (Fisheye) 2992×2992 / 2192×2192 / 1280×1280 / 640×640 / 320×320 (Quad PTZ) 1600x1200 / 1280×960 / 800×600 / VGA / QVGA •Quad streams mode (4:3) (Single PTZ (Quad streams)) 1280×960 / 800×600 / VGA / QVGA (max. 30 fps/25 fps) (Quad PTZ) 3584x2688 / 2560×1920 / 2048×1536 / 1600×1200 / 1280×960 / 800×600 / VGA / QVGA (max. 30 fps/25 fps) •Quad streams mode (16:9) (Single PTZ (Quad streams)) 1920×1080 / 1280x720 / 640x360/ 320x180 (max. 30 fps/25 fps) (Quad PTZ) 3840x2160 / 2560x1440 / 1920x1080 / 1280x720 / 640x360 / 320x180 (max. 30 fps/25 fps)

Resolution <Wall>	•Panorama mode (max. 30 fps/25 fps) 3840x2160 / 2560x1440 / 1920x1080 / 1280x720 / 640x360 / 320x180 •Fisheye + Panorama mode (max. 30 fps/25 fps) (Fisheye) 2992x2992 / 2192x2192 / 1280x1280 / 640x640 / 320x320 (Panorama) 1920x1080 / 1280x720 / 640x360 / 320x180
H.265/H.264 Transmission Priority/Type	[Transmission priority] Constant bit rate/ VBR/ Frame rate/ Best effort [Transmission type] Unicast port (AUTO)/ Unicast port (MANUAL)/ Multicast
No. of Stream	4
JPEG (MJPEG)	Image Quality:10 steps
Smart Coding	[GOP(Group of pictures) control] Off/ Low (Variable GOP 1s-8s)/Mid (Variable GOP 4s-16s)/ Advanced (Fixed GOP 60 seconds with 1 second Key frame)/ Frame rate control (Variable GOP 4s-16s with frame rate control) *Advanced and Frame rate control are only available with H.265. [Smart VIQS] On (High)/ On (Low)/ Off [Smart P-picture control] On/Off
Audio Compression Method *2	G.726 (ADPCM): 16 kbps/ 32 kbps G.711: 64 kbps AAC-LC *: 64 kbps/ 96 kbps/ 128 kbps
Audio Transmission Mode	Off / Mic (Line) input / Audio output / Interactive (Half duplex) / Interactive (Full duplex)
Supported Protocol	IPv6: TCP/IP, UDP/IP, HTTP, HTTPS, SSL/TLS, SMTP, DNS, NTP, SNMPv1/v2/v3, DHCPv6, RTP, MLD, ICMP, ARP, IEEE 802.1X, DiffServ, FTP, SFTP, LLDP, MQTT IPv4: TCP/IP, UDP/IP, HTTP, HTTPS, SSL/TLS, RTSP, RTP, RTP/RTCP, SMTP, DHCP, DNS, DDNS, NTP, SNMPv1/v2/v3, UPnP, IGMP, ICMP, ARP, IEEE 802.1X, DiffServ, SRTP, FTP, SFTP, LLDP, MQTT
No. of Simultaneous Users	Up to 14 users (Depending on network conditions)
Secure	FIPS 140-3 level 3, CC EAL6+ (NXP® EdgeLock® SE052F), Device Certificate GlobalSign® pre-installed, HTTPS, User authentication, digest authentication, Host authentication, IEEE802.1X, System log, Image transmission log, brute-force protection, Alteration Detection, Secure boot, Signed firmware
SDXC/SDHC/SD Memory Card (Option)	microSDXC memory card: 64 GB, 128 GB, 256 GB, 512 GB microSDHC memory card: 4 GB, 8 GB, 16 GB, 32 GB microSD memory card: 2 GB
Mobile Terminal Compatibility	iPad / iPhone (iOS 8.0 or later), Android™ terminals
ONVIF®Profile	G / M / S / T

Alarm	
Alarm Source	3 terminals input, VMD alarm, SCD alarm, Command alarm, Audio detection alarm, Casing open detection
Alarm Actions	SDXC/SDHC/SD memory recording, E-mail notification, HTTP alarm notification Indication on browser, TCP alarm notification output, MQTT alarm notification, FTP/SFTP image transfer, SNMP trap notification

Input/Output	
Built-in Microphone	Nondirectional electret condenser microphone (removable)
Audio Input *3	[For microphone] Recommended applicable microphone : Plug-in power type (Sensitivity of microphone: -48 dB±3 dB (0 dB=1 V/Pa, 1 kHz)) Input impedance: Approx. 2 kΩ (unbalanced) Supply voltage: 2.5 V ±0.5 V [For line] Input level: Approx. -10 dBV
Audio Output *3	ø3.5 mm stereo mini jack (Audio output is monaural.) Output impedance: Approx. 600 Ω (unbalanced) Output level: -20 dBV

External I/O Terminals *3	ALARM IN1 (Alarm input 1/ Black & white input/ Auto time adjustment input) (x1) ALARM IN2 (Alarm input 2/ ALARM OUT) (x1) ALARM IN3 (Alarm input 3/ AUX OUT) (x1)
Monitor Output	Yes(for adjustment) Φ3.5mm stereo mini jack NTSC or PAL signal can be output from camera (either press the INITIAL SET button quickly (within 1 second) or use software to select NTSC or PAL signal)
General	
Safety	UL62368-1 3Ed, CAN/CSA C22.2 NO.62368-1-19, IEC62368-1 3Ed.
EMC	FCC Part15 Subpart B, ClassA, SDoC, ICES-003 Issue 7 ClassA, EN55032:2015/A11 ClassA, EN55035:2017/A11
Power Source / Power Consumption *3	[Power Source] DC12V DC24V PoE (IEEE802.3af compliant) [Power Consumption] DC12 V :930mA / Approx. 11.2W DC24 V :470mA / Approx. 11.2 W PoE DC 48 V : 240 mA / Approx. 11.5 W (Class 0 device)
Ambient Operating Temperature	-10 °C to +50 °C {14 °F to +122 °F}
Ambient Operating Humidity	10 % to 90 % (no condensation)
Water and Dust Resistance	IP44
Dimensions	ø154 mm × 62mm (H) {ø6-1/16 inches × 2-7/16 inches (H)} (excluding RJ45 network cable and standard accessories other than attachment plate)
Mass (approx.)	Approx. 1.35 kg (2.98 lbs) (including attachments)
Finish	Main body: Aluminum die cast, i-PRO white Outer fixing screws: Stainless steel (Corrosion-resistant treatment)
Easy Kitting	Yes

NOTES

- *1 For information on the operation verification of the web browsers, refer to our support website <Control No.: C0132>.
- *2 When recording audio on an SD memory card, only use AAC-LC (Advanced Audio Coding - Low Complexity) .
- *3 The audio output can be switched to the monitor output. Refer to the “Operating Instructions” on our support website for descriptions of how to switch the output.
- *4 Refer to our technical information website <Control No.: C0106> for further information about Power source and Power consumption information.

Important

- Safety Precautions: Carefully read the Basic Information, Installation Guide and Operating Instructions before using this product.
- i-PRO Co., Ltd. cannot be held responsible for the performance of the network and/or any third-party products (including applications) used on the network.
- Masses and dimensions are approximate.
- Specifications are subject to change without notice.

Trademarks and registered trademarks

- iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. – Android is a trademark of Google LLC.
 - ONVIF is a trademark of ONVIF, Inc.
 - All other trademarks identified herein are the property of their respective owners
- ©i-PRO Co., Ltd All rights reserved / March 2026

OPTIONAL ACCESSORIES

Select a compatible accessory

[Accessory Selector \(i-pro.com\)](http://i-pro.com)



WV-QWL500-W
Mount Bracket



WV-QPL500-W
Mount Bracket



WV-QJB507-W
Mount Bracket



WV-QJB501-W
Base Bracket



WV-QJB501A-W
Base Bracket



WV-QJB501A-B
Base Bracket



WV-QJB500-W
Mount Bracket



WV-QCN500-W
Mount Bracket



WV-QCL100-W
Mount Bracket



WV-Q105A
Mount Bracket



WV-QCA503
I/O Cable for Security
radar



WV-SDB256G
i-PRO SD Memory
Card



WV-SDB128G
i-PRO SD Memory
Card



WV-SDB064G
i-PRO SD Memory
Card



WV-SDB032G
i-PRO SD Memory
Card



WV-PM500
Compact microphone
unit



WJ-PU201P
PoE Injector



WJ-PU201F/G
PoE Injector




WJ-PU201/G
PoE Injector



WV-QDC510C
Dome Cover

APPEARANCE



Important

- Safety Precautions : Carefully read the Basic Information, Installation Guide and Operating Instructions before using this product.
- i-PRO Co., Ltd. cannot be held responsible for the performance of the network and/or other manufacturers' products used on the network.
- Masses and dimensions are approximate.
- Specifications are subject to change without notice.

Trademarks and registered trademarks

- iPad and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries. – Android is a trademark of Google LLC.
 - ONVIF is a trademark of ONVIF, Inc.
 - All other trademarks identified herein are the property of their respective owners.
-