



CAT5 USB Server Interface Module TK-CAT5U (v1.0R)

- Connects a TRENDnet CAT5 KVM switch to a computer
- Requires an available USB and VGA computer port
- Supports CAT5, 5e and 6 cables
- One TK-CAT5U is required per computer

TRENDnet's CAT5 USB Server Interface Module, model TK-CAT5U, connects a TRENDnet CAT5 KVM switch to a computer with an available USB and VGA port. One TK-CAT5U is required per computer. CAT5, 5e, and 6 cable connections are supported.



Features



Computer

Connects a TRENDnet CAT5 KVM switch to a computer



VGA

Requires an available VGA port on the connected computer



Cable Support

Supports CAT5, 5e, and 6 cable connections



HD Resolution

Supports resolution up to 1600 x 1200 pixels



USB

Requires an available USB port on the connected computer



OS Support

Supports Windows®, Linux™, and Mac® operating systems

Specifications

Interface

- 10/100 Mbps Ethernet port (networked to CAT5 KVM switch)
- USB 2.0 male connector (Keyboard/Mouse connection to computer)
- VGA male connector (VGA connection to computer)

Resolution

• Up to 1600 x 1200 pixels

Operating Temperature

• 0 - 40 °C (32 - 104 °F)

Operating Humidity

• Max. 90% non-condensing

Dimensions

• Cable length 40 cm (15.7 in.)

Weight

• 48 g (1.7 oz.)

Warranty

• 2 year limited

Certifications

- CE
- FCC

Supported Cables

• CAT5, 5e, 6

Package contents

• TK-CAT5U