


WIRING DIAGRAM(568B)



NOTE:

1. ELECTRICAL TEST:

- (1). 100% OPEN SHORT, MISS WIRE TEST
- (2). INSULATION RESISTANCE:DC 300V 10MΩ ;
- (3). CONDUCTOR RESISTANCE:3Ω Max (More than 3m, add one ohm per meter) ;

2. Fluke channel link test:

TEST LIMIT:ISO11801 Channel Class Ea

3. PRINT WORD:

CAT6A S/FTP 4x2x27AWG/7 LSZH ISO11801 & EN50173 & ANSI/TIA568C.2

4. ROHS2.0 & REACH COMPLIANT

5. Minimum of the bending radius is 50mm
(Suitable for all meters)

COLOUR:GRAY (RAL 7035)		
ITEM NO.	LENGTH	TOLERANCE
21.99.0864	0.3m	±10mm
21.99.0860	0.5m	±15mm
21.99.0861	1m	±30mm
21.99.1990	1.5m	±45mm
21.99.0862	2m	±60mm
21.99.0863	3m	±90mm
21.99.0865	5m	±150mm
21.99.0866	7m	±210mm
21.99.0867	10m	±300mm
21.99.0868	15m	±450mm
21.99.0869	20m	±600mm

ITEM NO.	21.99.0864	21.99.0860	21.99.0861	21.99.1990	21.99.0862
	21.99.0863	21.99.0865	21.99.0866	21.99.0867	21.99.0868
	21.99.0869				
DESC.	VALUE S/FTP CAT.6a Patch Cord, gray				

MATERIAL LIST

③	OVER MOLD	PVC 75A GRAY(RAL 7035)	2	
②	CONNECTOR	RJ45 8P8C Shielded Plug, Pin Gold Plated 3u", Shell Nickel Plating, Transparence blue	2	
①	CABLE	S/FTP CAT. 6A 27AWG (Bare Copper*1P+AL-FOIL)*4PAIRS+BRAID (AL-MG) COLOUR:GRAY/RAL 7035 JACKET:LSZH OD:6.0±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT'Y	REMARK
		NEW		2018-11-21 A
BY	CHK	REVISION RECORD MODIFICATION		DATE REV.

SECOMP