

11990-202 ATCA SYSTEM 450/40 SERIES, 6 SLOT, DC, REPLICATED MESH, BUSSED IPMB









KEY FEATURES

Conforms to AdvancedTCA Standard PICMG 3.0 rev. 3.0

Input voltage -48 VDC/-60 VDC, two redundant power entry modules (PEM), can optionally be equipped with 2 redundant AC PEMs and up to 4 AC PSUs

Two hot swap fan trays, airflow from right to left (push/pull cooling), air filter access from front

450 W cooling capacity per slot at an ambient temperature of 55 °C

Prepared for one shelf alarm panel and two SCHROFF shelf managers with Pigeon Point ShMM 700

UL recognized, E229721 type T12

PRODUCT ATTRIBUTES

Product Type: System

Number of Slots: 6

Type: 19" Rack Mount

Backplane Type: Triple Replicated Mesh, Bussed IPMB
Data Transfer: 40 GbE
Power per Slot: 450 W
Input Voltage DC: -48 V; -60 V
Airflow Direction: Right to Left
Rack Height: 6 U
Power Supply Type: (2) DC PEM
Power Supply Included: Yes
Rear I/O: Yes
Complies With: PICMG 3.0 R3.0
Depth: 406 mm

ADDITIONAL PRODUCT DETAILS

The nVent SCHROFF ATCA 450/40 Series is a family of AdvancedTCA Shelves that provide cooling and power per slot for 450 W blades. The backplane is verified in accordance to 40GBASE-KR4 for 40 Gbit Ethernet.

Modified systems available on request.

Completely assembled, cabled and tested.



COMPLIAN

CERTIFICATIONS

North America

All locations +1.763.422.2661 Chat with us: schroff.nvent.com

Europe

Straubenhardt, Germany +49.7082.794.0 Betschdorf, France +33.3.88.90.64.90 Warsaw, Poland +48.22.209.98.35 Assago, Italy +39.02.932.7141 Chat with us: schroff.nvent.com

Asia

Shanghai, China +86.21.2412.6943 Qingdao, China +86.532.8771.6101 Singapore +65.6768.5800 Shin-Yokohama, Japan +81.45.476.0271 Chat with us: schroff.nvent.com

nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

Middle East & India

Dubai, United Arab Emirates +971.4.378.1700 Bangalore, India +91.80.6715.2001 Istanbul, Turkey +90.216.250.7374 Chat with us: schroff.nvent.com



© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

Our powerful portfolio of brands:

nVent reserves the right to change specifications without notice.