

11990-605 ATCA SYSTEM 300/40 SERIES, 14 SLOT, AC, DUAL STAR, RADIAL IPMB



KEY FEATURES

Conforms to AdvancedTCA Standard PICMG 3.0 rev.3.0

Input voltage 200-...-240-VAC, 3 x IEC 320-C20 AC mains plugs (please order AC plug-in power supply unit separately); 3 slots for 3 plug-in PSUs for 2-+-1-redundancy operation

Redundant hot-swap fan trays, airflow from bottom front to top rear; air filter access from front

300 W cooling capacity per slot at an ambient temperature of 55-°C

Prepared for two SCHROFF shelf managers with Pigeon Point ShMM-700

Shelf alarm panel (SAP) and shelf alarm display (SAD)

UL recognized, E229721 type T10

PRODUCT ATTRIBUTES

Product Type: System

Number of Slots: 14

Type: 19" Rack Mount
Backplane Type: Dual Star, Radial IPMB
Data Transfer: 40 GbE
Power per Slot: 300 W
Input Voltage AC: 200 – 240 V
Airflow Direction: Front to Rear
Rack Height: 14 U
Power Supply Type: (3) AC PSU
Power Supply Included: No
Rear I/O: Yes
Complies With: PICMG 3.0 R3.0
Depth: 472 mm

ADDITIONAL PRODUCT DETAILS

The nVent SCHROFF ATCA 300/40 Series is a family of AdvancedTCA Shelves that provide cooling and power per slot for 300 W blades. The backplane is verified in accordance to 40GBASE-KR4 for 40 Gbit Ethernet.

Modified systems available on request.

Completely assembled, cabled and tested.



CERTIFICATIONS

North America

All locations +1.763.422.2661 Chat with us: schroff.nvent.com

Europe

Straubenhardt, Germany +49.7082.794.0 Betschdorf, France +33.3.88.90.64.90 Warsaw, Poland +48.22.209.98.35 Assago, Italy +39.02.932.7141 Chat with us: schroff.nvent.com

Asia

Shanghai, China +86.21.2412.6943 Qingdao, China +86.532.8771.6101 Singapore +65.6768.5800 Shin-Yokohama, Japan +81.45.476.0271 Chat with us: schroff.nvent.com

nVent.com CADDY ERICO HOFFMAN RAYCHEM SCHROFF TRACER

Middle East & India

Dubai, United Arab Emirates +971.4.378.1700 Bangalore, India +91.80.6715.2001 Istanbul, Turkey +90.216.250.7374 Chat with us: schroff.nvent.com



© 2023 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners.

Our powerful portfolio of brands:

nVent reserves the right to change specifications without notice.